

防碾压食品排吸管CRATOS

A5-004



应用:

- 柔软的胶管，具有特殊增强层材料，在意外挤压后可恢复原状，常用于装卸罐车中的油型和非油型食物的重力流输送，压力输送或抽吸作业。

优点:

- 在意外挤压后可恢复原状
- 内管符合FDA/USDA食品认证及3-A卫生标准中18-03要求
- 白色光滑食品级内壁能有效抑制细菌滋长
- 良好的耐温性
- 不含塑化剂（邻苯二甲酸酯）

技术参数:

- 内胶：白色的乙烯基丁腈橡胶
- 增强层：多层合成纤维螺旋缠绕并带有单根PET螺旋丝增强
- 外胶：蓝色的乙烯基丁腈橡胶，表面布纹
- 工作温度：- 32°C 至 +110°C

适用标准及认证:

- GB4806.11-2016
- GB31604.30-2016
- FDA/USDA
- 3-A sanitary standard 18-03

Applications:

- A flexible hose with a special reinforcement material that can be recovered after accidental extrusion. For gravity flow, pressure, or suction service transferring oily and non-oily edibles from tank truck.

Advantages:

- Able to recover its shape after accidental squeeze
- Inner tube complies with FDA/USDA compliant and conforms to 3-A sanitary standard 18-03
- The smooth, seamless, white, multipurpose food grade tube that can restrain effectively bacterial to grow
- Good resistance to high temperature
- Phthalate free

Technical description:

- Tube: White synthetic rubber (FDA/USDA compliant and conforms to 3-A sanitary standard 18-03)
- Reinforcement: Spiral-plyed synthetic fabric with Monofilament Helix
- Cover: Blue synthetic rubber, wrapped
- Temperature range: - 32°C to +110°C

Standard/Approval:

- GB4806.11-2016
- GB31604.30-2016
- FDA/USDA
- 3-A sanitary standard 18-03

防碾压食品排吸管 CRATOS

产品编码 No.	内径 in	内径 mm	外径 mm	工作压力 bar	爆破压力 bar	耐负压 bar	弯曲半径 mm	重量 kg/m	包装长度 m
CRATOS-0750	3/4"	19.0	34.8	20.7	82.8	0.9	63	0.89	60.96
CRATOS-1000	1"	25.4	41.1	20.7	82.8	0.9	76	1.13	60.96
CRATOS-1250	1-1/4"	31.8	47.5	20.7	82.8	0.9	89	1.35	60.96
CRATOS-1500	1-1/2"	38.1	53.6	20.7	82.8	0.9	102	1.58	60.96
CRATOS-2000	2"	50.8	67.5	20.7	82.8	0.9	178	2.06	60.96
CRATOS-2500	2-1/2"	63.5	81.5	20.7	82.8	0.9	254	2.67	60.96
CRATOS-3000	3"	76.2	98.8	20.7	82.8	0.9	305	4.21	60.96

