

铂金硫化钢丝硅胶管-加强型 PURE SW-P



应用:

- 食品、饮料、化妆品、制药等高洁净行业, 可耐一定真空, 可进行CIP及SIP清洗。

技术参数:

- 铂金硫化硅胶管, 4层编织, 内置 SS316 不锈钢丝增强
- 标准为透明, 可定制其他颜色
- 工作温度: -60°C 至 +200°C

适用标准及认证:

- FDA, USP, BFR, European Pharmacopeia 3.1.9
Journal Officiel Brochure 1227

Applications:

- For food, beverages, cosmetics, medicine, pharmaceutical industries. It is recommended for vacuum. Suitable for CIP and SIP cleaning.

Technical Description:

- Manufactured from High purity platinum cured Silicone with AISI 316 stainless steel helix and 4 layers of polyester reinforcement
- Transparent (Coloured covers available)
- Temperature range : -60°C to +200°C

Standard/Approval:

- FDA, USP, BFR, European Pharmacopeia 3.1.9
Journal Officiel Brochure 1227

铂金硫化钢丝硅胶管-加强型 PURE SW-P

| 产品编码 No. | 内径 in mm | 外径 mm | 工作压力 bar | 爆破压力 bar | 真空度 bar | 弯曲半径 mm | 重量 kg/m | 包装长度 m | |
|----------------|----------------|----------|-------------|-------------|------------|------------|------------|-----------|---|
| PURE SW-P-0500 | 1/2" | 12.7 | 27 | 10 | 40 | 0.90 | 45 | 0.4 | 4 |
| PURE SW-P-0630 | 5/8" | 15.8 | 31 | 10 | 40 | 0.90 | 50 | 0.6 | 4 |
| PURE SW-P-0750 | 3/4" | 19.05 | 33.4 | 10 | 40 | 0.90 | 65 | 0.7 | 4 |
| PURE SW-P-1000 | 1" | 25.4 | 39.5 | 10 | 40 | 0.90 | 80 | 0.88 | 4 |
| PURE SW-P-1250 | 1-1/4" | 31.8 | 45.5 | 10 | 40 | 0.90 | 120 | 1 | 4 |
| PURE SW-P-1500 | 1-1/2" | 38.1 | 52.4 | 10 | 40 | 0.90 | 150 | 1.41 | 4 |
| PURE SW-P-2000 | 2" | 50.8 | 65.5 | 10 | 40 | 0.90 | 180 | 1.66 | 4 |
| PURE SW-P-2500 | 2-1/2" | 63.5 | 75.9 | 10 | 40 | 0.90 | 220 | 1.9 | 4 |
| PURE SW-P-3000 | 3" | 76.2 | 88.6 | 4 | 16 | 0.90 | 250 | 2.43 | 2 |
| PURE SW-P-4000 | 4" | 101.6 | 114 | 3 | 12 | 0.90 | 360 | 2.95 | 2 |

