


# 食品清洗管 BLUE WASHING

## A5-015

Supflow BLUE WASHING With Micro



### 应用:

- 高品质的产品构造, 可用于食品加工厂、乳品间、包装车间、装瓶厂、啤酒厂、罐头厂和乳酪厂高达212°F (100°C) 的热水清洗作业。

### 优点:

- 外胶具有超强耐磨和耐油性, 能够为抑制油品和动物脂肪的不良影响提供最大程度的保护
- 胶管外层中内嵌了抗菌保护材料
- 符合FDA要求的白色内管
- 很好的耐高温性能
- 不含塑化剂

### 技术参数:

- 内胶: 白色丁腈合成橡胶, 符合FDA
- 增强层: 螺旋合成纱线缠绕
- 外胶: 蓝色丁腈合成橡胶, 高耐油性并带有抗菌保护材料
- 工作温度: -29°C 至 +100°C

### 适用标准及认证:

- FDA 21CFR 177.2600、GB4806.11-2016、GB31604.30-2016

### Applications:

- A high-quality construction for hot water up to 212°F (100°C) for cleanup service in food processing plants, dairies, packing houses, bottling plants, breweries, canneries and creameries.

### Advantages:

- Its super abrasion and oil-resistant cover provides maximum protection against the adverse effects of oil and animal fats
- The cover of Blue Washing hose incorporates antimicrobial built-in product protection
- The white tube is comprised of FDA-compliant materials
- Very good resistance to high temperature
- Phthalate free

### Technical description:

- Tube: White FDA-compliant NBR synthetic rubber
- Reinforcement: Spiral synthetic yarn
- Cover: Blue NBR synthetic rubber, High Oil Resistance with product protection
- Temperature Range: -29°C to +100°C

### Standard/Approval:

- FDA 21CFR 177.2600、GB4806.11-2016、GB31604.30-2016

## 食品清洗管

## BLUE WASHING

产品编码 No.	内径		外径 mm	工作压力 bar	爆破压力 bar	重量 kg/m	包装长度 m
	in	mm					
BLUE WASHING-0375	3/8"	9.5	17.5	20	80	0.30	152.4
BLUE WASHING-0500	1/2"	12.7	22.8	20	80	0.45	152.4
BLUE WASHING-0625	5/8"	15.8	26.9	20	80	0.62	152.4
BLUE WASHING-0750	3/4"	19.1	30.2	20	80	0.65	152.4
BLUE WASHING-1000	1"	25.4	38.1	20	80	0.95	137.16

