

氟橡胶蠕动泵管

9140



应用:

- 腐蚀性化学转移
- 氯化, 氟化化学转移
- 化学和分析分析

优点:

- 对醇类, 酸类, 卤代溶剂具有出色的耐受性
- 在TUV Nord审核的10000级洁净室中制造和包装
- 双层塑料袋, 标准包装长度为7.6米
- 提高火焰和防火性能
- 提供60 Shore A和70 Shore A硬度

技术参数:

- 材质: 氟橡胶
- 工作温度: -15°C至+250°C
- 适用标准及标准: FDA、USP Class VI、RoHS、BPA Free、TSE/BSE Free、Phthalate Free、Plasticizer Free

灭菌方法:

- γ 射线, 高温高压灭菌, 环氧乙烷

Applications:

- Corrosive chemical transfer
- Chlorinated, fluorinated chemical transfer
- Chemical and analytical analysis

Advantage:

- Excellent resistance to alcohols, acids, halogenated solvents.
- Manufactured and packaged in clean room of class 10000 facility audited by TUV Nord
- Double polybag packaged in standard package length is 7.6 meters
- Greater flame and fire resistance
- Available in 60 Shore A & 70 Shore A hardness

Technical description:

- Tube: FKM Rubber
- Temperature: -15°C to +250°C
- Standard/Approval: FDA、USP Class VI、RoHS、BPA Free、TSE/BSE Free、Phthalate Free、Plasticizer Free

Sterilization methods:

- Gamma、SIP、ETO

氟橡胶蠕动泵管 9140

产品编码 No.	内径 mm	外径 mm	壁厚 mm	包装长度 m
9140-13	0.8	4	1.6	7.62/15
9140-14	1.6	4.8	1.6	7.62/15
9140-15	4.8	9.6	2.4	7.62/15
9140-16	3.2	6.4	1.6	7.62/15
9140-17	6.4	9.6	1.6	7.62/15
9140-18	7.9	11.1	1.6	7.62/15
9140-19	2.4	5.6	1.6	7.62/15
9140-24	6.4	11.2	2.4	7.62/15
9140-25	4.8	8	1.6	7.62/15
9140-26	6.4	12.7	3.2	7.62/15
9140-35	7.9	12.7	2.4	7.62/15
9140-36	9.6	14.4	2.4	7.62/15
9140-70	9.6	19.1	4.8	7.62/15
9140-73	9.6	16	3.2	7.62/15
9140-82	12.7	19.1	3.2	7.62/15
9140-86	9.6	22.4	6.4	7.62/15
9140-87	12.7	25.4	6.4	7.62/15
9140-88	12.7	22.4	4.8	7.62/15
9140-89	15.9	25.4	4.8	7.62/15
9140-91	19.1	31.8	6.4	7.62/15
9140-92	25.4	35	4.8	7.62/15

