

食品饮料输送软管

A3-012



应用:

- BLAUDIECK LGD适用于各种食品行业饮料行业酿酒行业的各类输送

技术参数:

- 内层: 黑色, 三元乙丙橡胶
- 强化层: 多层合成线绳
- 外层: 黑色EPDM, 表面光滑
- 温度范围: -40°F 到 +212°F (-40°C 到 +100°C)
- 工作压力: 200psi (具体看口径)
- 安全系数: 4:1

Applications:

- GST® II hose is a versatile general purpose hose designed to handle air, mild chemicals and water. The hose construction incorporates a tube that is compatible with light oil mists found in air tool lubricating systems, and the multiple plies of textile reinforcement provide flexibility. The cover is resistant to abrasion, heat and ozone, and is available in multiple standard colors for color-coded identification

Technical description:

- Tube: Black EPDM; ARPM Class C oil resistance
- Reinforcement: Multiple textile plies
- Cover: Black
- Temp Range: -40°F to +212°F (-40°C to +100°C)
- Design Factor: 4:1
- Packaging: Reels; cartons

食品饮料输送软管

BLAUDIECK LGD

产品编码 No.	内径 in	mm	外径 mm	工作压力 bar	爆破压力 bar	弯曲半径 mm	重量 kg/m	包装长度 m
A3-012-0500	1/2	13	21	10	≥ 40	80	0.280	40
A3-012-0630	5/8	16	24	10	≥ 40	100	0.320	40
A3-012-0750	3/4	19	29	10	≥ 40	115	0.500	40
A3-012-1000	1	25	37	10	≥ 40	150	0.800	40
A3-012-1250	1-1/4	32	48	10	≥ 40	195	1.400	40
A3-012-1500	1-1/2	38	56	10	≥ 40	230	1.700	40
A3-012-1575	1-9/16	40	58	10	≥ 40	240	1.900	40
A3-012-2000	2	50	70	10	≥ 40	300	2.700	40
A3-012-2380	2-3/8	60	80	10	≥ 40	420	3.000	40
A3-012-2560	2-9/16	65	89	10	≥ 40	455	3.800	40
A3-012-3000	3	75	99	10	≥ 40	525	4.100	40
A3-012-3150	3-1/8	80	108	10	≥ 40	560	5.100	40
A3-012-4000	4	100	130	10	≥ 40	700	6.700	40

blueFuture

您身边的工业专家