

## 食品输送管 A4-112



### 应用:

- 一种高科技, 柔软波浪形状已证明具有好的性能的胶管。也可提供更佳性价比, 没有波浪的胶管。
- 对于超级柔软性更有如下可以称赞:
- 灵活操作: 易于在很紧凑的空间搬进搬出
- 轻质: 易于抬举及搬运
- 低的弯曲力: 易于连接与拆卸, 具有高的生产效率

### 技术参数:

- 内层: 白的Chemivic合成橡胶 (符合FDA、USDA及3A的18-03)
- 增强层: 多层合成纤维缠绕带有镀锌螺旋钢丝
- 外层: 白色或灰色Chemivic波浪形合成橡胶 (包裹压印)
- 温度: - 25° F 至212°F (- 32°C 至 100°C)
- 包装: 成卷及薄膜包装
- 软管标识: Goodyear® Plicord® ExtremeFlex™ Food Grade 150 Psi WP

### Applications:

- A high-tech, flexible corrugated hose with pretzel-like agility and proven performance. Best of all, it's available at a non-corrugated price, making it a great value. With ExtremeFlex, there's even more to appreciate:
- Flexible Handling: Easier to move in and out of tight spaces and around sharp corners
- Lightweight: Easier to lift and carry, so there are fewer workplace injuries
- Lower Force to Bend: Easier to connect and disconnect, keeping productivity high

### Technical description:

- Tube: White Chemivic™ synthetic rubber (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03)
- Reinforcement: Spiral-plied synthetic fabric with galvanized wire helix
- Cover: White or gray Chemivic™ corrugated synthetic rubber (wrapped impression)
- Temperature: - 25°F to 212°F (- 32°C to 100°C)
- Packaging: Coiled & polywrapped
- Branding: Example: Goodyear® Plicord® ExtremeFlex™ Food Grade 150 PSI WP

## 食品输送管 PLICORD EXTREMEFLEX FOOD GRADE

产品编码 No.	内径		外径 mm	工作压力 bar	耐负压 in	重量 kg/m
	in	mm				
A4-112-2000	2	51.2	62.0	10.3	29	1.48
A4-112-3000	3	76.1	89.9	10.3	29	2.79
A4-112-4000	4	102.1	116.6	10.3	29	3.98

**blueFuture**  
您身边的工业专家